IFDR.E497000 Low-voltage Lighting Systems, Power Units, Luminaires and Fittings

Page Bottom

Low-voltage Lighting Systems, Power Units, Luminaires and Fittings

See General Information for Low-voltage Lighting Systems, Power Units, Luminaires and Fittings

RISINGSUN PHOTOELECTRIC HOLDINGS LIMITED

E497000

NO 4 3 FLOOR E DISTRICT HUAFENGGAOXIN INDUSTRIAL PARK NO 3 TECHNOLOGY ROAD PINGSHAN NEW DISTRICT SHENZHEN, GUANGDONG 518118 CHINA

LED Low Voltage Luminaire, Class 2 LED Strip, Model(s) RS-2216-B-C-D-E-F series, RS-2835-B-C-D-E-F series, RS-3014-B-C-D-E-F series, RS-3528-B-C-D-E-F series, RS-5050-B-C-D-E-F series

- A Can be 2216, represent LED type.
- B Can be 12V or 24V, represent voltage. ?12V: DC12V, 24V: DC24V.?
- C Can be 030, 060, 080, 108, 112, 120, 140, 144, 210, 216, 240, 256, 288 or 480, represent the number of LED per meter. For examples, ? 030: 30 LEDS Per meter, 240: 240 LEDS per meter, 480: 480 LEDS per meter.?
- D Can be 03, 05, 06, 08, 10, 12, 15 or 24, represent width of PCB. ?03: 3mm, 05: 5mm, 06: 6mm, 08: 8mm, 10: 10mm, 12: 12mm, 15: 15mm, 24: 24mm.?
- E Can be 20, 65, 67 or 68, represent water proof method. ?20: Bare Board, 65: Wrap bare LED strip by drip silicone glue, 67: Wrap bare LED strip by silicone tube, then drip silicone glue, 68: Wrap bare LED strip by silicone tube, then fully fill in silicone tube.?
- F Can be W, CW, WW, Y, R, G, B, P, V, A, RGB, RGBW or RGBWWW, represent LED color. ?W: White, CW: Cool White, WW: Warm White, Y: Yellow, R: Red, G: Green, B: Blue, P: Far Red, V: Purple, A: Amber, RGB: Integrate of Red, Green and Blue, RGBW: Integrate of Red, Green, Blue and White, RGBWWW: Integrate of Red, Green, Blue, White and Warm White.?

Last Updated on 2018-03-14

<u>Questions?</u> <u>Print this page</u> <u>Terms of Use</u> <u>Page Top</u>

♦ 2018 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2018 UL LLC".