


PRODUCT DATA SHEET



CCT Adjustable Series
2216 416 LEDs/m 18W/m 12mm



RS-CA2216-24V-416D-12-20




 Product Features

1. Source by high output 2216Led with uniform illumination
2. High Brightness, Efficiency, Customized Wattage, Luminous Flux per M
3. Tunable white 2700-6500K


 CCT Option



 IP Rating Option



 Dimensions




Note:

LED strip length tolerance is + -0.2%mm.
Width tolerance is + -0.2%mm.
Size of each section is 38.46mm.
DC 24V

 **Diagram**

Dimension (mm)

| Length/Reel | Width | Height | Min. Cutting  |
|-------------|-------|--------|--|
| 5000 | 12 | 1.45 | Every 38.46mm (16 LEDs) |

 **Data**

| Part Number | Working Voltage | Power (W/m) | Current (A/m) | LED Qty/m | CRI |
|--------------------------|-----------------|-------------|---------------|-----------|-----|
| RS-CA2216-24V-416D-12-20 | 24V | 18W/m | 0.75A/m | 416 | 90+ |

| CCT (°K) | Luminous Efficiency | lumen/m |
|------------|---------------------|----------|
| 2700K(9W) | 114lm/W | 1026lm/m |
| 4000K(18W) | 117lm/W | 2106lm/m |
| 6500K(9W) | 127lm/W | 1143lm/m |


Note:

The data base on IP20 non-waterproof.
The Lumen output value tolerance + -5% due to testing way.
The CCT will be + -100k tolerance.


Absolute Maximum Ratings

| Parameter | Symbol | Value | Units |
|---------------------------|--------|---------|-------|
| Thermal Measurement Point | Tc | 80 | |
| Operating Temperature | Topr | -20~+40 | °C |
| Storage Temperature | Ts | -20~+80 | |
| Number of FPC Connection | | | |


Wiring Diagram Application




Packaging



! Cautions



<50mm diameter of wrapped object prohibited



Pls wear the electrostatics ring for avoid ESD

✓ Safety & Disclosures

1. Do not install the led strip in environment where excessive heat may occur.
2. Do not extend beyond the recommended maximum run length.
3. Only use copper wiring. Use wires rated for at least 176°F(80°C) and certified for use with external connection of electrical equipment.
4. Do not install IP20 LED strip products in outdoor / wet location environments.
5. Excessive handling, bending, and pressure may damage the product, voiding the warranty.
6. Improper wire selection and installation could overheat wires, and cause fire.
7. Do not connect directly to high voltage or AC power.
8. Installation must be in accordance with local and national electrical code regulations.
9. To ensure safety and correct installation, our strips are intended to be installed by a qualified, licensed electrician.